Product Standard Specifications For

Classic Cowhide
Performance Rating = 5.0

Product:	Classic Cowhide
Description:	Top Grain, Cowhide, Aniline Dyed
Average Hide Size:	55 – 60 SF
Thickness:	1.1mm (+/- 0.2mm)

Testing:

Meets the following standards:

Flammability:	(Must be Specified on the PO)
	IMO Finishes & Furnishings (2010 FTP) MSC 88/26
	Part 5: Surface Flammability [was A.653 (16)]
	Part 8: Upholstered Furniture [was A.652 (16)]
	FAR 25.853(a)(I)(ii) - 12 Second Vertical
	FAR 25.853(a)(I)(i) - 60 Second Vertical
	Cal TB 117
	NFPA 260 Class 1
	BS5852 Crib 5
Water Spotting:	IUF420 - No Staining
Crocking:	ASTM D5053 - minimum 3 on AATCC Greyscale
Federal Blocking:	ASTM D6116 - No Adhesion of Finish
Arm Rub Welt:	Townsend LM7 - No Finish Break Through
Wyzenbeek Welt:	Townsend LM13 - No Change in Color
Adhesion:	Townsend LM5 - No Removal of Finish
Taber:	ASTM D3884 H18 250g 300 Cycles – No Change in Color
Accelerated Aging:	Townsend LM2 - minimum 3 on AATCC Greyscale, No Cracking

Revision 4