



Test Report # MANCHESTER-0001-82515

TOWNSEND LEATHER NFPA 260 COVER FABRIC BURN REPORT

Date: 8/25/2015

Conditioning Chamber: Time In: 11:25am Time Out: 3:30pm
8/24/2015 8/25/2015

THICKNESS: 1.0 - 1.2 MM

Specimen: Townsend Leather Manchester Cowhide

Standard Filling Material: Non FR polyurethane foam, density 20 kg/m³ to 25 kg/m³

Test

Table with 3 columns: Specimen # (Seconds), Ignition (yes/no/SE), Char Length on Vertical Panel (mm). Rows 1-3.

Retest

Table with 3 columns: Specimen # (Seconds), Ignition (yes/no/SE), Char Length on Vertical Panel (mm). Rows 1-3.

Retest 2

Table with 3 columns: Specimen # (Seconds), Ignition (yes/no/SE), Char Length on Vertical Panel (mm). Rows 1-3.

CLASS I [checked] CLASS II [unchecked]

Tested according to NFPA 260 : 2013 Edition-Section 6.1 Cover Fabric Test

Dawn Finch

Quality Control

Townsend Leather Co. Inc.

45-49 Townsend Ave PO Box 669

PO Box 669

Johnstown, NY 12095

This form is electronically signed. If you need an actual signature, please call.