



Test Report # SOFTSUEDECOW-0001-63017

TOWNSEND LEATHER NFPA 260 COVER FABRIC BURN REPORT

Date: 6/30/2017

Conditioning Chamber: Time In: 11:05 AM Time Out:
6/29/2017 6/30/2017

THICKNESS: 1.0 - 1.2 MM

Specimen: Townsend Leather Soft Suede Cowhide
(Additional Flametreatment)

Standard Filling Material: Non FR polyurethane foam, density 20 kg/m³ to 25 kg/m³
Test

Table with 3 columns: Specimen # (Seconds), Ignition (yes/no/SE), Char Length on Vertical Panel (mm). Rows 1-3.

Retest Table with 3 columns: Specimen # (Seconds), Ignition (yes/no/SE), Char Length on Vertical Panel (mm). Row 1.

Retest 2 Table with 3 columns: Specimen # (Seconds), Ignition (yes/no/SE), Char Length on Vertical Panel (mm). Rows 1-3.

CLASS I [checked] CLASS II []

Tested according to NFPA 260 : 2013 Edition-Section 6.1 Cover Fabric Test

Dawn Finch

Quality Control
Townsend Leather Co. Inc.
45-49 Townsend Ave PO Box 669
PO Box 669
Johnstown, NY 12095

This form is electronically signed. If you need an actual signature, please call.